

Philips Halogen Long Life MRI6 Lamps

Long Life Low-Voltage Halogen Reflector Lamps



Photography Copyright: Mark Ballogg

Ideal for retail stores, hotels, restaurants, museums and art gallery lighting

▶ **Optimized Coil, Burner and Reflector Design**

Has maximum efficiency for reduced energy consumption and provides bright, white light and superior beam quality

▶ **Up To 20 Layers of Dichroic Coating**

Consistent coating quality lamp to lamp and throughout lifetime

▶ **UV Block**

Reduces color fading

▶ **6000 Hour Rated Average Life¹**

Has double the life of comparable standard halogen lamps and delays replacement frequency, which will save on re-lamping costs

▶ **Universal Burning Position**

▶ **Variety of Wattages and Beam Spreads**

¹) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.



PHILIPS

Philips Halogen Long Life MRI 6 Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Ordering Code	Watts	Volts	Pkg Qty.	Description	Bulb Type	Base	Rated Avg. Life (Hrs.) ¹	Approx. MBCP ²	Lumens	Class, Filament	MOL (In.)
37814-1	20MRC16/SP10 ESX	20	12	50	Spot 10°	MRC-16	GU5.3	6000	5000	310	C, CC-8	1½
26966-2	20MRC16/NFL24 BBF	20	12	50	N. Flood 24°	MRC-16	GU5.3	6000	1700	320	C, CC-8	1½
37815-8	20MRC16/FL36 BAB	20	12	50	Flood 36°	MRC-16	GU5.3	6000	780	320	C, CC-8	1½
14054-1	35MRC16/SP10	35	12	50	Spot 10°	MRC-16	GU5.3	6000	8000	680	C, CC-8	1½
14052-5	35MRC16/NFL24	35	12	50	N. Flood 24°	MRC-16	GU5.3	6000	3100	690	C, CC-8	1½
14053-3	35MRC16/FL36	35	12	50	Flood 36°	MRC-16	GU5.3	6000	1500	710	C, CC-8	1½
37816-6	50MRC16/SP10 EXT	50	12	50	Spot 10°	MRC-16	GU5.3	6000	13,000	920	C, CC-8	1½
14061-6	50MRC16/SP15	50	12	50	Spot 15°	MRC-16	GU5.3	6000	8000	930	C, CC-8	1½
37817-4	50MRC16/NFL24 EXZ	50	12	50	N. Flood 24°	MRC-16	GU5.3	6000	4400	960	C, CC-8	1½
37818-2	50MRC16/FL36 EXN	50	12	50	Flood 36°	MRC-16	GU5.3	6000	2200	960	C, CC-8	1½
37808-3*	75MRC16/SP10 EYF	75	12	50	Spot 10°	MR-16	GU5.3	6000	14,000	1320	C, CC-8	1½
37809-1*	75MRC16/FL36 EYC	75	12	50	Flood 36°	MR-16	GU5.3	6000	2500	1410	C, CC-8	1½

Shipping Data (Subject to change without notice)

Product Number	SKU UPC (0 46677-)	Outer Bar Code (5 004677-)	Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H) (In.)	Case Dimensions (W x D x H) (In.)	Pallet Dimensions (W x D x H) (In.)
37814-1	37814 1	37814 6	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
26966-2	26966 1	26966 6	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37815-8	37815 8	37815 3	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
14054-1	14054 0	14054 5	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
14052-5	14052 6	14052 1	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
14053-3	14053 3	14053 8	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37816-6	37816 5	37816 0	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
14061-6	14061 8	14061 3	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37817-4	37817 2	37817 7	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37818-2	37818 9	37818 4	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37808-3	37808 0	37808 5	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75
37809-1	37809 7	37809 2	50	4.3	0.29	8250	1650	5	1.77 x 1.77 x 2.17	4.19 x 12.06 x 9.75	36.18 x 46.09 x 48.75

1) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

2) Maximum Beam Candlepower.

CAUTION: THIS LAMP IS PRESSURIZED AND COULD SHATTER so to avoid injury and to avoid exposure to ultraviolet radiation, this lamp should be used in a fixture that provides a protective shield of tempered glass. Provide adequate ventilation to ensure that seal temperature does not exceed 350° C and use only in fixtures rated for the wattage stated on this package. To avoid risks of burns or other injury, turn power off and allow lamp to fully cool before attempting to replace. Socket condition may affect lamp life. Inspect and replace socket if deterioration has occurred.

* **CAUTION: DO NOT TOUCH INNER CAPSULE WITH BARE HANDS.** Fingerprints may result in shorter life. Remove fingerprints with alcohol. This lamp is pressurized and could shatter so to avoid injury and to avoid exposure to ultraviolet radiation, use only in fixtures that provide a protective shield of tempered glass. Provide adequate ventilation to ensure that seal temperature does not exceed 350°C and use only in fixtures rated for the wattage stated on this package. To avoid risks of burns or other injury, turn power off and allow lamp to fully cool before attempting to replace. Socket condition may affect lamp life. Inspect and replace socket if deterioration has occurred.

