

Philips Halogen MRCII Lamps

A Range of 35mm Low-Voltage Halogen Reflector Lamps



Photography by Laszlo Regos

► Consistent Color Coating

Consistent coating quality lamp to lamp and throughout lifetime

► 4000 Hour Rated Average Life¹

► UV Block

Reduces color fading

► Universal Burning Position

¹) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

Ideal for retail stores, hotels, restaurants, museums and art gallery lighting



PHILIPS

Philips Lighting Company
 200 Franklin Square Drive
 P.O. Box 6800
 Somerset, NJ 08875-6800
 1-800-555-0050

www.philips.com

Philips Lighting
 281 Hillmount Road
 Markham, Ontario
 Canada L6C 2S3
 1-800-555-0050
 A Division of Philips Electronics North America Corporation

A Division of Philips Electronics North America Corporation
 Printed in USA 07/05 P-5770

Philips Halogen MRC II Lamps

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Ordering Code	Watts	Volts	Pkg Qty.	Description	Bulb Type	Base	Rated Avg. Life, Hrs ¹	Approx. MBCP ²	Lumens	Class, Filament	MOL (In.)
37821-6	20MRC II/SP10 PRO FTB 20		12	50	Spot 10°	MRC-II	GU4	4000	4800	310	C, CC-8	1 5/8
37822-4	20MRC II/FL30 PRO FTD 20		12	50	Flood 30°	MRC-II	GU4	4000	690	320	C, CC-8	1 5/8

Shipping Data (Subject to change without notice)

Product Number	SKU UPC (0 46677-)	Outer Bar Code (5 004677-)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H) (In.)	Case Dimensions (W x D x H) (In.)	Pallet Dimensions (W x D x H) (In.)
37821-6	37821 9	37821 4	50	2.43	0.22	9750	1950	5	1.57 x 1.57 x 2.17	5.06 x 8.75 x 8.69	39.11 x 45.54 x 43.45
37822-4	37822 6	37822 1	50	2.43	0.22	9750	1950	5	1.57 x 1.57 x 2.17	5.06 x 8.75 x 8.69	39.11 x 45.54 x 43.45

1) Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

2) Maximum Beam Candlepower.

CAUTION: THIS LAMP IS PRESSURIZES AND COULD SHATTER so to avoid injury and to avoid exposure to ultraviolet radiation, this lamp should be used in a fixture that provides a protective shield of tempered glass. Provide adequate ventilation to ensure that seal temperature does not exceed 350°C and use only in fixtures rated for the wattage stated on this package. To avoid risks of burns or other injury, turn power off and allow lamp to fully cool before attempting to replace. Socket condition may affect lamp life. Inspect and replace socket if deterioration has occurred.

