



Philips Lighting Company

MATERIAL SAFETY DATA SHEET

Revised: 6/01

PRODUCT: Fluorescent Lamp (Cool Green)

SECTION 1: MANUFACTURER

Manufacturer's Name and Address: Philips Lighting Company
A Division of Philips Electronics
North America Corporation
200 Franklin Square Drive
Somerset, N. J. 08875-6800

Emergency Telephone No.: (800) 424-9300 CHEMTREC
(732) 563-3197 SAFETY AND COMPLIANCE

Other Information Calls: (732) 563-3490

SECTION 2: HAZARDOUS INGREDIENTS

	OSHA PEL	ACGIH TLV	PERCENTAGE
Inert ingredients (glass, aluminum, etc.)			approx. 97% by wgt.
Phosphor powder*			approx. 3% by wgt.
nuisance dust	15mg/m ³	10mg/m ³	
fluorides*(16984-48-8)	2.5mg/m ³	2.5mg/m ³	approx. .01% by wgt.
antimony*(7440-37-0)	.5mg/m ³	.5mg/m ³	approx. .01% by wgt.
manganese*(7439-96-5)	5mg/m ³ (c)	5 mg/m ³	approx. .02% by wgt.
Mercury(7439-97-6)	.1 mg/m ³	.025 mg/m ³	approx. .01% by wgt.
	Ceiling	8 hr. TWA	
Zinc Silicate (1314-13-2)	5mg/m ³	5mg/m ³	approx 1% by wgt.

*These materials are tightly bound within the calcium phosphate crystal matrix.



A division of
Philips Electronics North America Corporation

200 Franklin Square Drive
P.O. Box 6800
Somerset, NJ 08875-6800
Tel: 732.563.3000

SECTION 3: PHYSICAL CHEMICAL CHARACTERISTICS

Not applicable. This item is a light bulb. Up to 8 foot long and up to 1.5 inches in diameter.

SECTION 4: FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION DATA NOT APPLICABLE. UNDER EXTREME HEAT GLASS ENVELOPE MIGHT MELT OR CRACK.

SECTION 5: REACTIVITY DATA

Stability: Lamp is stable
Incompatibility: Glass will react with Hydrofluoric Acid
Polymerization: Not applicable

SECTION 6: HEALTH HAZARD DATA

Not applicable for the intact lamp. Breakage of the lamp may result in some exposure to the phosphor powder dust/and to elemental mercury vapor. No adverse affects are expected from occasional exposure to broken lamps, but as a matter of good practice, prolonged or frequent exposure should be avoided through the use of adequate ventilation during disposal of large quantities of lamps.

EMERGENCY AND FIRST AID PROCEDURE: Normal first aid procedure for glass cuts if such occur through lamp breakage.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

Normal precautions should be taken for collection of broken glass.

Waste Disposal Method: At the end of rated life, when this lamp is removed from service, it will, when subjected to the current Toxic Characteristic Leaching Procedure (TCLP) prescribed by the Environmental Protection Agency for determining whether an item is a hazardous waste be listed as a non-hazardous waste under current E. P. A. definition. Philips Lighting will provide the test protocol on request. This result will allow the end user to evaluate all of the disposal option, which may be available in the particular state in which the generator facility is located.

SECTION 8: CONTROL MEASURES

Respiratory Protection: None. NIOSH-approved respirator might be used if large volumes of lamps are being broken for disposal.

Ventilation: Avoid inhalation of any airborne dust. Provide local exhaust when disposing large quantities of lamps.

Hand and Eye Protection: Appropriate hand and eye protection should be worn when disposing of lamps or handling broken glass.

S06-96003